

Program LEQ Professional v. 6-2016 dla Windows

Projekt: Stanisław Labuda -Raport dla dz. 74/4 obr. Nożynko, gm., Czarna Dąbrówka
Beznazwy

Dane do obliczeń :

Współczynnik gruntu (całego obszaru analizy)-global G = 0.000
Temperatura otoczenia 10[°C]

Źródła punktowe

Nr	X[m]	Y[m]	z[m]	Pma	Symbol
=====					
1	618.0	824.0	0.0	80.0	WEN1
2	628.0	834.0	3.0	80.0	WEN2
3	640.0	846.0	3.0	80.0	WEN3
4	650.0	858.0	3.0	80.0	WEN4
5	662.0	874.0	3.0	80.0	WEN5
6	674.0	884.0	3.0	80.0	WEN6
7	690.0	904.0	3.0	80.0	WEN7
8	704.0	922.0	3.0	80.0	WEN8
9	588.0	788.0	3.0	80.0	WEN9
10	580.0	776.0	3.0	80.0	WEN10
11	570.0	766.0	3.0	80.0	WEN11
12	554.0	750.0	3.0	80.0	WEN12
13	544.0	738.0	3.0	80.0	WEN13
14	536.0	724.0	3.0	80.0	WEN14
15	520.0	710.0	3.0	80.0	WEN15
16	506.0	690.0	3.0	8.0	WEN16
17	612.0	808.0	3.0	91.0	SIL1
18	612.0	804.0	3.0	91.0	SIL2
19	604.0	798.0	3.0	91.0	SIL3
20	608.0	796.0	3.0	91.0	SIL4
21	462.0	682.0	0.5	54.0	PT-H
22	476.7	702.0	0.5	63.0	PT-S
23	491.3	722.0	0.5	57.0	PT-M1
24	506.0	742.0	0.5	57.0	PT-M2
25	520.7	762.0	0.5	57.0	PT-M3
26	535.3	782.0	0.5	57.0	PT-M4
27	550.0	802.0	0.5	57.0	PT-M5
28	564.7	822.0	0.5	57.0	PT-M6
29	579.3	842.0	0.5	54.0	PT-H1
30	594.0	862.0	0.5	63.0	PT-S1
=====					

Źródła typu hala produkcyjna :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
=====										
1	704.0	942.0	608.0	824.0	620.0	808.0	720.0	928.0	8.0	8.0
2	588.0	802.0	486.0	682.0	494.0	670.0	602.0	790.0	8.0	8.0
=====										

POZIOMY HAŁASU i IZOLACYJNOŚĆ PRZEGRÓD

Nr źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
=====											
1	sc.1	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Nr źródła		A	63	125	250	500	1000	2000	4000	8000	wsp.odb.
=====											
2	sc.1	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.2	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.3	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	sc.4	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R sc	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	
	dach	L wew	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	1.0000
		R d	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	

Pasy zieleni :

WSPÓŁRZĘDNE WIERZCHOŁKÓW :

Nr	X1[m]	Y1[m]	X2[m]	Y2[m]	X3[m]	Y3[m]	X4[m]	Y4[m]	h0[m]	h[m]
=====										
1	690.0	1158.0	784.0	972.0	880.0	1072.0	798.0	1174.0	10.0	10.0
2	800.0	1230.0	794.0	1178.0	886.0	1070.0	952.0	1160.0	10.0	10.0
3	756.0	932.0	748.0	940.0	484.0	632.0	486.0	618.0	10.0	10.0
4	562.0	1212.0	472.0	912.0	490.0	908.0	580.0	1208.0	10.0	10.0

Punkty obserwacji

Nr	Symbol	X[m]	Y[m]	z[m]

1	P0-1	1086.0	1792.0	1.5
2	P0-2	1006.0	1244.0	1.5
3	P0-3	742.0	1258.0	1.5
4	P0-4	528.0	1306.0	1.5
5	P0-5	484.0	968.0	1.5
6	P0-6	488.0	618.0	1.5